

Heavy Duty Cleaner

PROPERTIES

- ▶ Industrial strength glass cleaner
- ▶ Non-smearing, economical and fast acting
- ▶ Leaves surfaces with a brilliant shine and free from static
- ▶ Non tainting liquid

APPLICATIONS

- Allows easy removal of contaminants such as nicotine, atmospheric grime, oily deposits, finger marks, dust and uncured sealant
- Designed specifically for use on glass, windows, mirrors, tiling, stainless steel and chrome

PROCESSING

Application Method

Lightly spray 15 – 20 cm away from the surface to be cleaned. Wipe over using a clean lint free cloth, then buff to a sparkling clear finish.

Storage

Store upright in cool dry conditions.

LIMITATIONS OF USE

It is the user's responsibility to determine suitability. A compatibility test is recommended on a hidden area of the surface prior to application.

CHARACTERISTICS

State	Liquid
Colour	Blue
Odour	Perceptible odour
Evaporation rate	Negligible
Oxidising	Non-oxidising by EC criteria
Solubility in H ₂ O	Soluble
Boiling point	100 °C
Flash point	60 - 93
Relative Density	0.922 at 24°C

Technical Datasheet
Version 09.09.2017
Pages 2



PACKAGING

UniBond Trade 133 is supplied in 1L bottles.

Product and packaging disposal

Dispose of waste and residues in accordance with local authority requirements (please refer to Safety Data Sheet for more information).

Heavy Duty Cleaner

HEALTH & SAFETY



WARNING

Causes serious eye irritation. Wash hands thoroughly after handling. Wear eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists, seek medical attention.

Safety Advice

Consult the Material Safety Data Sheet (mymstds.henkel.com) for UniBond Trade 133. www.unibond-trade.co.uk

"The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. f.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law."

Henkel AG & Co. KGaA

40191 Düsseldorf, Germany

Elch GmbH

Henkelstrasse 67 – D-40589 Düsseldorf

HPSA Ltd.

Hinckley, Leics. – LE10 1DP

Henkel Limited

Road 5, Winsford Industrial Estate, Winsford, Cheshire, CW7 3QY

www.unibond-trade.co.uk